



# icofond

## Product description

Viscous, thixotropic, cold asphalt in water dispersion.

## Uses

- Anti-dust primer for torch-on bitumen roofing membranes.
- Waterproof protection for foundations and retaining walls, roofing and below-grade timber structures.
- Protection of botanical grafts.

## Features / Benefits

- Low cost, eco-friendly bonding primer.
- Easy to use.
- Compatible with cement-based mortars.

## Surface preparation

- Clean thoroughly and remove dust, loose material or non-adhering particles, grease, oil and any contaminant that may affect proper adhesion.

## Application instructions

- As a protective coating: Apply ICOFOND by roller or brush at a rate of 0.5 Kg/m<sup>2</sup> per coat. If applied to concrete surfaces, prime with a coat of ICOFOND diluted with 20-30% water at a rate of 300-350 gr/m<sup>2</sup>.
- As a primer for bitumen membranes: apply ICOFOND diluted with water in a 1:1 ratio.
- Tools can be cleaned with water or nitro solvents.

## Precautions

- Do not apply where water may pond.
- Apply at temperatures above +10°C.
- Do not apply in case of rain, fog or dew.



PRODUCT FEATURE	MEASURE	UNIT
Type of product	one component	
Density	1.02 (± 0.05)	Kg/L
Solid content	44 (± 2%)	%
Brookfield viscosity	3860	mPa
Full drying (+23°C ± 3°C)	12	hours
Spread rate per coat	0.5	Kg/m <sup>2</sup>
Coverage (as protective coating)	1	Kg/m <sup>2</sup>
Theoretical thickness	0.3 (at 1 kg/m <sup>2</sup> )	mm
Dilution	Ready to use	
pH	7.3 (±2%)	
Shelf Life	12	months

## Safety measures

- See SDS.

## Storage

- Store in a dry, well-ventilated place at temperatures above freezing.

## Color



Black



Please contact our technical support at:  
[assistenza@icobititalia.com](mailto:assistenza@icobititalia.com)

Ensure that the TDS is up to date: the latest version can be viewed and downloaded at [icobit.com](http://icobit.com). The manufacturer reserves the right to amend product specifications without notice. The above performances were measured according to the standards in force at the time of issue and represent the average results of our tests. Although highly reliable, they do not constitute a binding commitment nor liability for Icobit Italia S.r.l. The purchaser and the end consumer acknowledge responsibility for the product suitability to the intended use.



**ICOBIT ITALIA SRL**  
 Viale Luca Gaurico 9/11 00143 Roma (Italy)  
 C.F e P.I. 12428711001  
[www.icobit.com](http://www.icobit.com) | [info@icobititalia.com](mailto:info@icobititalia.com)

## PACKAGING



## APPLICATION METHOD



BRUSH



ROLLER



AIRLESS