

risanaterrazze



Product description

Non-filming, clear waterproof treatment for terraces and balconies.

Uses

Waterproof protection for terraces and balconies made of stoneware, terracotta, clinker, concrete, porphyry and masonry in general.

Features / Benefits

- Hydrophobic.
- Clear: it protects from water without affecting the original appearance.
- Reduces the formation of efflorescence and moss on the grout.
- Also effective on marble, travertine and granite.
- Retards oil absorption.
- Seals cracks and fissures in the substrate.
- Ready to use.

Surface preparation

- Clean thoroughly and remove dust, loose material or non-adhering particles, grease, oil, efflorescence and any contaminant that may affect proper adhesion.
- Remove and replace any loose or missing tile portions.
- Repair cracked or missing tile grout.

Application instructions

- Apply by brush or roller to clean, dry surface. Avoid foaming.
- Linger over tile grouts and damaged or highly absorbent areas.
- Highly absorbent substrates such as cement surfaces, masonry or terracotta may require a second coat 12 hours after the first coat.
- Excess product should be removed with a cloth during application, or by washing with water and a floor degreaser after 48 hours.
- Protect from rain for 24 hours from application.

Precautions

- Ensure that the substrate is completely dry.
- Salt efflorescence must be treated beforehand.
- Do not apply indoors or in areas with limited air circulation.
- Mask off your windows and any surfaces you don't want to be painted: RISANATERRAZZE is hard to remove once cured.
- Always test on an inconspicuous spot before applying to natural stone.



PRODUCT FEATURE	MEASURE	UNIT
Type of product	one component	
Density	0.79 (\pm 0.03)	Kg /Lt
Curing time (+23 °C; 50% R.H.)	24	hours
Number of coats	min. 1	
Coverage per coat on tiled surfaces	\approx 10	m ² /Lt
Application temperature	from +5°C to +35°C	
Shelf life	12	months

Safety measures

- See SDS.

Storage

- Store in a dry, well-ventilated place.

Colors



Clear


Please contact our Technical Support at: assistenza@icobititalia.com

The manufacturer reserves the right to amend product specifications without notice. The above performances were measured according to the standards in force at the time of issue and represent the average results of our tests. Although highly reliable, they do not constitute a binding commitment nor liability for Icobit Italia S.r.l. The purchaser and the end consumer acknowledge responsibility for the product suitability to the intended use.



ICOBIT ITALIA SRL
 Viale Luca Gaurico 9/11 00143 Roma (Italy)
 C.F e P.I. 12428711001
www.icobit.com | info@icobititalia.com

PACKAGING



APPLICATION METHODS



ROLLER



BRUSH