

## TECHNICAL DATA SHEET

# icopas p



### Product description

Bonding primer for ICOPAS, ICOPAS HP, ICOPAS AR, made from bitumen, elastomers and highly volatile solvents.

### Features / Benefits

- Penetrating agent for concrete substrates.
- Anti dusting.

### Uses

Pore filler for absorbent substrates specified for treatment with ICOPAS, ICOPAS HP, ICOPAS AR.

### Surface preparation

- Clean thoroughly and remove dust, loose material or non-adhering particles, grease, oil and any contaminant that may affect proper adhesion or penetration.

### Application instructions

- Product is ready to use and must not be diluted with universal solvents, which would alter its properties.
- Once dry, apply the liquid waterproofing membrane after not less than 2 hours and not more than 24.

### Application methods

- Airless, roller, brush.

## SPECIFICATIONS

PRODUCT FEATURE	MEASURE	UNIT
Typee of product	one component	
Diluition	ready to use	
Density	0,95 (± 0,05)	Kg/Lt
Full dry at + 23°C (±3°C) breezy	2	hrs
Strati prescritti	1	
Consumo per strato	0.2 ÷ 0.3	Kg/m <sup>2</sup>
Color	black	
Shelf life	12	Months



Please contact our technical support at:  
[assistenza@icobititalia.com](mailto:assistenza@icobititalia.com)

Ensure that the TDS is up to date: the latest version can be viewed and downloaded at [icobit.com](http://icobit.com).  
The manufacturer reserves the right to amend the product specifications without notice.  
The above performances were measured according to the standards in force at the time of issue and represent the average results of our tests. Although highly reliable, they do not constitute a binding commitment nor liability for Icobit Italia S.r.l. The purchaser and the end consumer acknowledge responsibility for the product suitability to the intended use.



**ICOBIT ITALIA SRL**  
Via V. Veneto 54b 00187 Roma (Italy)  
VAT No.12428711001  
[www.icobit.com](http://www.icobit.com) | [info@icobititalia.com](mailto:info@icobititalia.com)

ICOPAS P 0325