

# versol



## Product description

Ready-to-use primer made from bitumen and high-volatility solvents. Bituminous tar.

## Uses

- Bonding primer for waterproofing with bitumen membranes.
- Protective paint for piping and for timber or concrete structures.



## Features / Benefits

- Excellent bonding strength.
- Quick drying.
- Easy to apply.

## Precautions

- Apply to completely dry substrates.
- Do not use the blowtorch before VERSOL has thoroughly dried.
- Use only in well-ventilated areas.



## Surface preparation

- Clean surface thoroughly and remove dust, loose material or non-adhering particles, grease, oil and anything that may affect proper bonding.

## Application instructions

- Apply at a rate of approx. 200 gr/m<sup>2</sup> (actual coverage dependent on substrate porosity and absorption).
- Drying time is affected by ambient temperature.
- Ensure that pass-through elements such as HVAC and piping are properly sealed.
- For residential roofing, the use of VERAP water-based primer is recommended.
- As a bituminous tar, apply at approx. 300 gr/m<sup>2</sup> (actual coverage dependent on substrate porosity and absorption).
- Tools may be cleaned with ICODIL SX.



PRODUCT FEATURE	MEASURE	UNIT
Type of product	one component	
Density	0.94 ( $\pm 0,05$ )	Kg/Lt
Solid content	59 ( $\pm 2\%$ )	%
Tack free (at +23°C, 50% R.H.)	60	min
Dust free (at +23°C, 50% R.H.)	120	min
Number of coats	1	
Spread rate per coat (according to substrate)	$\approx 200$	gr/m <sup>2</sup>
Coverage (according to substrate)	5	m <sup>2</sup> /Kg
Dilution	ready to use	
Color	black	
Shelf Life	18	months

## Safety measures

- See SDS.

## Storage

- Store in cool, dry, well-ventilated areas away from heat sources. Keep container tightly sealed.

## Color



Please contact our technical support at:  
[assistenza@icobititalia.com](mailto:assistenza@icobititalia.com)

Ensure that the TDS is up to date: the latest version can be viewed and downloaded at [icobit.com](http://icobit.com)  
The manufacturer reserves the right to amend product specifications without notice. The above performances were measured according to the standards in force at the time of issue and represent the average results of our tests. Although highly reliable, they do not constitute a binding commitment nor liability for Icobit Italia S.r.l. The purchaser and the end consumer acknowledge responsibility for the product suitability to the intended use.



**ICOBIT ITALIA SRL**  
Via Vittorio Veneto, 54b – 00187 Roma (RM)  
C.F e P.I. 12428711001  
[www.icobit.com](http://www.icobit.com) | [info@icobititalia.com](mailto:info@icobititalia.com)

## PACKAGING



## TOOLS



BRUSH



ROLLER



AIRLESS